GILGAL Power Systems Ltd.

Military Power Supply

Model: GIL-74103H-A0

Up to 33w output power
9Vdc to 32Vdc Input Voltage
Output Voltage : 3.3V



Features

- Insolated Output voltage.
- Wide input voltage range 9VDC to 32VDC.
- Remote on/off.
- Reverse input voltage protection. Auto recovery.
- Output Current limit.
- Wide temperature range -40°C to +65°C.
- High efficiency.
- Protection against surge & spikes per MIL-STD-1275A&B, MIL-STD-704A÷F.
- Protection against conducted susceptibility and radiated susceptibility per MIL-STD-461.
- Decreases input line Susceptibility emission per MIL-STD-461, CS101.
- Vibration withstand according to MIL-STD-810.

Applications

- Automotive
- Laptop Adapter
- Industrial
- Military



Figure 1: Block Diagram

® All rights reserved to Gilgal Power Systems Ltd.

Specification (at 25°C, 75% load, 28V nominal voltage, unless otherwise specified)

PARAMETER	
Input	
Nominal input voltage:	28v
Input range	9v ÷ 36v
Reverse input protect	Automatic Recovery
Enable	Yes (positive or negative, see how to order)
Meet MIL-1275A/B	Surge – 100v/50ms, 0.5Ω,
	Spikes – 250v/70us
Meet MIL-704A/F	Surge – 80v/75ms
	Spikes – 600v/10us
Meet DO160E cat A/Z	Surge – 80v/100ms
	Spikes – 600v/10us
Meet MIL-461F	CS-101, CS-106,
Output #1	
Output voltage	3.3V
Output power	Up to 33W (10Amp.)
Voltage trim	+/- 10% (only by manufacture)
Voltage Accuracy	+/- 1%
Line Reg. & Load Regulation	+/-2% max
Output ripple (10MHz)	20mVrms max
Output Current limit	Remove overload for recovery.
General	
Power Efficiency	86% typ.
Remote control	Yes (see how to order)
Insolated Output to Input	500vMin
Weight (typ.)	75 gr.
Environmental	
Temperature MIL-STD-810G, Methods 501.5,502.5	-40 + 65˚C , Operational Base Plate
	-40 + 95˚C , Storage
Vibration	MIL-STD-810G, Method 514.5
SHOCK ,MIL-STD-810G Method 516.5 –Ground equipment	SRS Shock of 40g's 15-23 msec @ cross over Freq - 45 Hz per Table 516.6-I , Operational
VIBRATION , MIL-STD-810G	
Trucks & Trailers. Transportation	Cat. 4. Secured Cargo Cat. 5. Loose Cargo (with its transit case)

Connector	Pin Number	Function	Description
INPUT	J1/1	Vin	+Input voltage
	J1/5	GND	Input Return
OUTPUT	J1/2	+3V3	Output voltage
	J1/6	+3V3	Output voltage
	J1/3	GND out	Output GND
	J1/7	GND out	Output GND
	J1/8	Un use	Un use
ON/OFF	J1/4	ENABLE	En control

Table 1: Pin Connection and function

® All rights reserved to Gilgal Power Systems Ltd.

Connector: MOLEX PN: **430450806.**
Dimensions: ±0.2
Mounting hole size: (4) Screw # 4/40



How to Order:

- GIL-74103H-A0 ,
- Enable: "On"= Leave open. "Off" = Short to GND. (V_{EN} (at "On") = 1.2v)

For other options and additional information please contact Gilgal.

General comments:

1. **Warranty: 2 year.**
2. Specification subject to change without notice.

Information furnished by Gilgal power systems believed to be accurate and reliable.
However, no responsibility is assumed for its use. Gilgal power systems make no representation that the interconnection of its circuits a described herein will not infringe on existing patent rights.
All information stated in this sheet is under the terms mentioned in the SLA on Gilgal's website – www.gilgalpower.com

® **All rights reserved to Gilgal Power Systems Ltd.**